

# Styropor® BF 222

## Expanded Polystyrene

### BASF Corporation

#### Product Description

Styropor BF products can be used in a wide variety of applications including blocks for panels, general insulation, below grade use, fabrication, flotation, and general packaging. Additional applications include insulated concrete forms, thin walled custom molding, and other general protective packaging.

Modified expandable polystyrene (EPS) containing approximately 6 wt% pentane as the blowing agent.

Styropor BF products are compatible with many anti-stat, mineral oil and color additives added during processing.

Block molding applications, low and high densities requiring excellent fusion or with regrind

#### General

Material Status	• Commercial: Active		
Availability	• Europe	• North America	
Additive	• Blowing Agent (6.0%) <sup>1</sup>		
Features	• Foamable		
Uses	• Flotation Devices	• Packaging	• Thin-walled Parts
	• Insulation	• Reinforced Panels	
Agency Ratings	• ASTM C 578, I	• ASTM E 84	
Forms	• Spheres		
Processing Method	• Injection Molding		

Physical	Nominal Value	Unit
Apparent Density	0.01 to 0.05	g/cm <sup>3</sup>
Moisture Content	< 1.2	%

Flammability	Nominal Value	Unit	Test Method
Flame Rating - UL	HF-1		UL 94
UL File Number	E54675		

Additional Information	Nominal Value	Unit
Bead Diameter (> 97%)	0.850 to 1.70	mm

#### Notes

<sup>1</sup> Pentane

<sup>2</sup> Typical properties: these are not to be construed as specifications.

Dongguan Yi-Ming Plastic Chemical Co., Ltd.

如需要更多物性资料请查阅 [www.kedisujiao.com](http://www.kedisujiao.com)

备注：以上原料物性数据由IDES发布, 我公司仅提供参考！数据如有变动，请联系原料生产厂家获知。我公司不承担任何法律责任！