

# Terblend® N NM-11 (Cond)

Polyamide 6 + ABS

BASF Corporation

## Product Description

Terblend N NM-11 is an ABS/PA6 blend combining very high impact strength, even at low temperatures, with an excellent processability and surface appearance.

## General

Material Status	• Commercial: Active
Availability	• North America
Features	• Good Processability • Good Surface Finish • High Impact Resistance
Agency Ratings	• ULC Unspecified Rating
RoHS Compliance	• RoHS Compliant
Forms	• Pellets
Processing Method	• Injection Molding

Mechanical	Nominal Value	Unit	Test Method
Tensile modulus	1600	MPa	ISO 527-2 <sup>2</sup>
Tensile Strength			
Yield, 23°C	32.0	MPa	ASTM D638
Yield	34.0	MPa	ISO 527-2 <sup>2</sup>
Break, 23°C	30.0	MPa	ASTM D638
Tensile Strain (Yield)	5.5	%	ISO 527-2 <sup>2</sup>
Nominal strain at break	> 50	%	ISO 527-2 <sup>2</sup>

Impact	Nominal Value	Unit	Test Method
Notched Izod Impact (23°C)	No Break		ASTM D256

Hardness	Nominal Value	Unit	Test Method
Ball Indentation Hardness	70.0	MPa	ISO 2039-1

Electrical	Nominal Value	Unit	Test Method
Volume Resistivity	> 1.0E+11	ohm·cm	ASTM D257

## Notes

<sup>1</sup> Typical properties: these are not to be construed as specifications.

<sup>2</sup> Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.

Dongguan Yi-Ming Plastic Chemical Co., Ltd.

如需要更多物性资料请查阅 [www.kedisujiao.com](http://www.kedisujiao.com)

备注：以上原料物性数据由厂家发布,我公司仅提供参考！数据如有变动，请联系原料生产厂家获知。我公司不承担任何法律责任！