

Terblend® N NMX04 (Cond)

Polyamide 6 + ABS

BASF Corporation

Product Description

Terblend N NMX04 is an ABS/PA6 blend specially developed for painted exterior applications, combining impact resistance with excellent processability and paintability.

General

Material Status	• Commercial: Active
Availability	• Europe • North America
Features	• Good Processability • High Impact Resistance • Paintable
RoHS Compliance	• RoHS Compliant
Forms	• Pellets
Processing Method	• Injection Molding

Mechanical	Nominal Value	Unit	Test Method
Tensile modulus	1600	MPa	ISO 527-2 ²
Tensile Stress (Yield)	32.0	MPa	ISO 527-2 ²
Tensile Strain (Yield)	5.5	%	ISO 527-2 ²
Nominal strain at break	> 50	%	ISO 527-2 ²

Hardness	Nominal Value	Unit	Test Method
Ball Indentation Hardness	70.0	MPa	ISO 2039-1

Notes

¹ Typical properties: these are not to be construed as specifications.

² Tested in accordance with ISO 10350. 23°C/50%r.h. unless otherwise noted.

Dongguan Yi-Ming Plastic Chemical Co., Ltd.

如需要更多物性资料请查阅 www.kedisujiao.com

备注：以上原料物性数据由厂家发布,我公司仅提供参考！数据如有变动，请联系原料生产厂家获知。我公司不承担任何法律责任！